SPECIFICATIONS PR #0933100 Page 1 of 1

| ITEM NO. | DESCRIPTION | CHECK IF AS SPECIFIED | DESCRIBE FULLY IF NOT AS SPECIFIED |
|-------------|--|-----------------------------|---------------------------------------|
| 1. | Engine, Marine, Complete, in-board Standard Rotation, 7.4L(454 ci) Vortec base Marine Engine (1986 or Later Application) | | |
| | Vendor to be located no more the 50 miles from Steilacoom, WA | | |
| | Complete Turn Key Engine | | |
| | 100% Brand new components | | |
| | At least 330 HP at the crank shaft | | |
| | Cast Iron 4 barrel intake manifold | | |
| | Holley 4175 marine carburetor (650 CFM) | | |
| | USCG approved flexible fuel line | | |
| | USCG approved electric fuel pump kit | | |
| | Oil pressure switch and oil sending unit | | |
| | Delco Voyager Ignition kit, Voyager distributor, HEI coil, spark plugs and wires, | | |
| | misc. wires for shaft interrupt switch. <i>Include all special timing tools</i> | | |
| | 14" inboard flywheel | | |
| | Mercruiser center-rise manifold with 4" riser | | |
| | Throttle bracket, throttle clip and quick connect ball joint | | |
| | 70 amp alternator, bracket and tensioner (USCG approved) | | |
| | USCG approved High torque Aft mount starter | | |
| | Engine wire harness w/universal 10 pin plug | | |
| | Water/fuel separator | | |
| | Thermostat housing w/thermostat | | |
| | Adjustable engine mounts | | |
| | Flame arrester and weather cover | | |
| | Dip stick tube, dip stick, and EZ oil drain hose | | |
| | Remote Oil Filter Kit | | |
| | Corrosion resistant urethane paint | | |
| | All pulleys, hoses, belts, installed | | |
| | Full fresh water cooling system kit (inboard) | | |
| | Engine to be run, timed and tested before delivery | | |
| | Warranty to be at least 2 years | | |